

Ruggedized Dome Camera

The P-RCD features a clear, full polycarbonate housing that protects the Panasonic WV-S6130 POE, IP dome camera and allows full view of the status indicators



P-RDC

- Impact resistant housing and dome of polycarbonate
- Quickly determine network connection status
- Easy maintenance
- V3i modular mounts install in seconds
- Proven field use track record during at power conditions in both PWR and BWR plants
- Built in Virginia, USA

Contact V3 Integrators, LLC

800-806-9041

Sales@v3is.com

463 Dinwiddie Ave
Waynesboro, Va 22980

Ruggedized Dome Camera

IPTZ Camera Applications


- General Area Viewing
- Refuel Floor
- SG Platforms
- Low Light Areas
- Under Vessel
- Condenser Bay
- Turbine Building
- Spent Fuel Pool
- Steam Tunnel
- Aux Building
- High Rad Areas
- Permanent Mounting



Specifications	
Optical/Image Sensor	
Resolution	HD 1080p 1920 x 1080
Optical Zoom	21x
Min. Illumination	Color .5 lx
Electrical	
Power	POE (802.3af)
Connections	
Camera	Cat5/6 ethercon
Pan and Tilt	
P&T Speed	Variable, Proportional
Pan Range	0 - 350°
Tilt Range	-20 - 90°
Physical	
Weight	3.5 lbs (no mount)
Width	6"
Height	8" (no mount)
Max Temp.	122°F
Lighting	NA
Video	H.264/MJPEG
Material	Polycarbonate/Delrin
Control/Viewing	
Genetec Security Center, Milstone, Onvif	



C-MCM "Claw" Clamp Mount



M-MCM Magnetic Mount



SC-MCM Safety Clamp Mount

Ordering information	
Description	Part Number
P-RDC Camera (WV-S6130 internal)	V100010
M-MCM Magnetic Camera Mount (carbon steel 1/4" minimum)	V100002
C-MCM Clamp Camera Mount (round tube 1-1.5")	V100003
P-MCM Plate Camera Mount (Converts to pole style mounts)	V100004
SC-MCM Safety Clamp Camera Mount (round, square tube)	V100490

Contact V3 Integrators, LLC

800-806-9041

Sales@v3is.com

463 Dinwiddie Ave
Waynesboro, Va 22980